



## AVIN SHIMI JAHAN

Avin Chemistry  
General Trading Company  
Iranian Bitumen Exporter

# MC30 Cutback Bitumen

### MC30 Specifications

Priming of all non-bituminous road bases

### Typical Physical & Performance Properties

	MC30	
<b>Application Rate</b>	From 0,6 litre per m2 to 1,2 litre/m2	
<b>Spraying/Application Temperature</b>	45° - 65° C	
<b>Ductility @ 25 deg. C.</b>	100 min	
<b>Appearance</b>	Black	
<b>Distillate, % by Vol. of Total Distillate to 360 C</b>	Min	Max
<b>to 190° C</b>	0	15
<b>to 225° C</b>	15	60
<b>to 260° C</b>	50	85
<b>to 316° C</b>	80	100
<b>Residue from Distillation to 360°C, % Vol. of Original Sample</b>	Min	Max
<b>Penetration at 25°C on Residue from Distillation</b>	90	180



Unit 11, 4th Floor, No.22, 6th Alley, Ahmad Ghasir St,  
Shahid Beheshti Av. Tehran - Iran



+98 - 21 - 88 17 08 22 - 7



+98 - 21 -88 17 08 28



+98 -912 - 220 13 95



info@avinchemistry.com